



EZ7252 Volatile Fatty Acids (VFA) & Alkalinity Analyser

Nr. produs: EZ7252.XXXXXXXXXX

RON Preț (fără TVA): Contact

Online, automatic monitoring of critical process parameters and process efficiency in anaerobic digesters

A new control alternative for anaerobic digestion

Due to the expensive or time-consuming character of most analysis methods for anaerobic processes, industrial digesters are usually not adequately monitored. Developed specifically for monitoring anaerobic digesters, the EZ7200 Series bring the possibility of implementing new control alternatives to typical operating problems in mid to large scale digesters.

Critical parameter monitoring, online and automatic

Anaerobic digesters require monitoring of a specific set of critical parameters in order to obtain optimal production efficiency, compliance and biogas yield. The primary parameter is volatile fatty acids (VFAs), representing the metabolic condition of the anaerobic digester and responding quickly to stress induced changes, combined with alkalinity.

The EZ7200 Series are easy-to-operate online titrators using a unique and robust method for measuring the critical process parameters in one single run, enabling insight as well as full control over the anaerobic process:

- Direct titration with minimum volatilisation
- Continuous monitoring of the anaerobic process
- Enabling higher loading rate for maximum CH₄ production
- Prevention of digester failure due to VFA accumulation
- Easy implementation within a dynamic control strategy
- Easy integration into corporate networks

There are many additional options available. Please contact Hach for more details.

Specificații

Alarma:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Calibrare:	Automatic; frequency freely programmable
Calitate proba:	Maximum particle size 500 µm, < 0.1 g/L
	Most applications require the use of an EZ9130 sampling/filtration system.

Certificări:	CE compliant / ETL certified
Clasa de protecție:	Analyser cabinet: IP44 / Panel PC: IP65
Conținutul cutiei:	EZ7252 VFA & Alkalinity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x pH Electrode, Routine S7 Connection, 2 x empty 10L Reagent Containers with Fittings (NaOH & H ₂ SO ₄ Solution) and 1 x empty 2.5L Reagent Container with Fittings (Anti-foam Solution)
Cuve:	10 - 15 minutes
Debitul probei:	100 - 300 mL/min
Demineralised water:	N.A.
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimensiuni (Înălțime x Lățime x Adâncime):	690 mm x 465 mm x 330 mm
Domeniu de măsurare:	VFAs 100 - 5000 mg/L as acetate equivalent; Alkalinity, total and Alkalinity, partial 250 - 5000 mg/L as CaCO ₃
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Esantion: presiune:	By external overflow vessel
Garanție:	24 luni
Greutate:	25 kg
Iesiri analogice:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferente:	Phosphates and similar dissociating ions and non-fatty acids which on acidification from undissociated acids may cause interference. Sulphide may deteriorate some types of pH electrodes. Fats, oil, proteins, surfactants and tar.
Limita de detecție:	≤ 10 mg/L
Material:	Hinged part: Thermoform ABS, door: PMMA Wall section: Galvanised steel, powder coated
Metoda de măsurare:	Acid-base titration
Nr. flux probe :	1, 2, or 4
Nume metoda:	Titrimetric
Parametru:	Volatile fatty acids (VFAs), total alkalinity
Precizie:	Better than 3% full scale range for standard test solutions
Putere:	100 - 240 VAC, 50/60 Hz Max. power consumption: 120 VA
Reagent Requirements:	Keep between 10 - 30 °C
Rinsing:	With tap water
Scurgere:	Atmospheric pressure, vented, min. Ø 32 mm
Temperatura ambiantă:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura probă:	10 - 30 °C
Validation:	Automatic; frequency freely programmable

Conținutul cutiei

EZ7252 VFA & Alkalinity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x pH Electrode, Routine S7 Connection, 2 x empty 10L Reagent Containers with Fittings (NaOH & H₂SO₄ Solution) and 1 x empty 2.5L Reagent Container with Fittings (Anti-foam Solution)